MOTOWRAP

Installing Instructions

Hi, Thanks for buying a graphics kit from Motowrap! Here are a few tips to get the decals on straight. The assembly of our kits is a bit demanding due to the strong adhesives and number of pieces. But just keep your head cold – and it will turn out perfect!

Tools needed:

- Heat gun (Could also work with a hair dryer, but it's not recommended)
- Plastic scraper (Included)
- A clean cloth, preferably microfiber
- Detergent

Before you get started... There are many great clips on Youtube about how to easily assemble your kit, search for Seadoo graphic! However, read through our entire instruction before you begin. **Good luck!**

Istart by removing any previous stickers as the contours of these will appear through the foil. You can do this by heating them up with the heat gun, then carefully picking up an edge and pulling them out. Be sure to clean your vehicle, especially in areas where there were previous sticker. Use a good detergent to remove grease. (Surface cleaner, brake cleaner)

2 Check carefully where each piece should be placed, it is quite easy to figure out.

Use a spray gun with water mixed with a drop of washing-up liquid (dish soap) and spray some on the scooter and on the back of the decal. This is to make it easier for you to fit the pieces together with each other as the soap makes it easier to lift the decal if it would get in the wrong place. The adhesive on these stickers is extra strong, making it very difficult to remove the pieces once you start applying them.

Apply a decal piece very lightly and see that it fits in with the other pieces. Once you get it perfectly in place, take the scraper (squeezer) and use its soft side to drag it from the center and outwards on the piece, - It's important to get out ALL the water and air. Now the sticker is pretty much permanent and can't be removed without being destroyed.

After all the pieces are placed and made "pretty much permanent", it's time to move on to "absolutely permanent" by applying heat to each piece with a heatgun. A good rule of thumb on how much heat to apply is to try it while your hand is on the decal, just when it starts to feel uncomfortable for your hand you have the right temperature. Hover about 10-15cm over each piece with the heatgun while applying pressure to it with your other hand, firmly pushing/stroking the decal piece.

Once that is done it's time to work on some extra treatment on the edges with about the same amount of heat, heat up the edge of the piece and apply pressure to it with you thumb. Press and stroke it outwards firmly with your thumb and work your way around the piece not missing anything, heating the edge as you go.

*If you notice a bubble somewhere on the decal you can get rid of it by punching a hole in it with a needle and then use the heat gun and push around the hole with your thumb to even it out.

DONE!

We'd be very happy if you could send us a picture of your finished result, or tag us on social media:



